

# POINTMAN



## nuvia™ Card Printer N15

Affordable printer for ID badges & Banks Card  
Single sided printer  
Smaller foot print & Light weight  
Secure Mag. Stripe encoding,  
Contact & Contactless smart card Encoding  
Rewrite function

## Features

Auto feed & Single hopper  
High Security: Kensington® physical lock  
multiple enclosure locks  
Compact design, light weight  
WIFI option & Mobile application

## Options

Magnetic stripe encoding(ISO or JIS2)  
Contact Smart card(Serial or PC/SC)  
Contactless smart card(Serial or PC/SC)  
Printer Lid lock  
Printer hopper lock  
Wi-Fi(User upgradable)

# Specifications

|  |                                     |   |
|--|-------------------------------------|---|
| Print  | Print Technology                    | Direct-to-card Dye-sublimation / Resin thermal transfer                 |
|  | Print Capabilities                  | Single edge-to-edge printing  |
|  |                                     | Full-color and monochrome printing capability                           |
|  |                                     | Alphanumeric text, logos and digitized signatures                       |
|  | Print Resolution                    | 300 dpi (11.8 dpm), 16.7 Million Color                                  |
|  | Print Speed*                        | Full-color Printing   |
|  |                                     | Single Side (YMCKO) 180 ~ 200 card/hour.                                |
|  |                                     | Monochrome up to 600 cards/hr.  |
|  | Card                                | PVC and composite PVC Cards   |
| Card format : ISO CR80-ISO7810 (53.98mm X 85.60mm),Card thickness : 0.4mm~1.2mm card |                                     |   |
| Automatic card feeding : up to 100 cards(0.76mm)                                     |                                     |   |
| Printer Encoding Option  | Magnetic Stripe Encoding            | ISO7811 (Track 1,2,3), Coercivity : HiCo/LoCo JIS II                    |
|  | Smart Card Personalization          | ISO7816, EMV Level 1(PC/SC or Serial)                                   |
|  | RF ID Card                          | Mifare, ISO 14443 A / B, Desfire, NFC, Felica (PC/SC or Serial)         |
|  | SAM                                 | PLCC 1 (Extra-2 Sockets), SIM 4 sockets                                 |
|  | Mobile Chip Card                    | ISO 7816  |
| Printer Specifications   | Dimensions                          | 366(L) × 184 (W) × 228 (H)mm  |
|  | Weight                              | 4.5kg   |
|  | Power                               | 100-240V ~ 50/60Hz 1.7A / Output : DC24V 2.5A                           |
|  | Font                                | True Type Fonts via Window Drivers                                      |
|  | Memory                              | 128 MB RAM  |
|  | Interface                           | USB2.0 (High-Speed), Built in 10/100 Ethernet                           |
|  | Operation System for Printer Driver | Windows Vista, Windows 7 & 8 & 10 Windows 2003/2008 server, 2012 server |
|  | Approvals                           | FCC Class A, CE (EN 55022 Class A, EN 55024), CCC, KCC Energy STAR RoHS |
|  | Software                            | Card Designer 2.0™ for Easy Printing                                    |
|  | Warranty                            | Printer - 2 years Printer Head - 2 years                                |